

BT 222 DHC

Ref.055216

Dataliner®

Multi function 12V Tester:

- ✓ **Battery**
- ✓ **Starter**
- ✓ **Alternator circuit**



Battery Test

✓ **Able to test many lead battery types :**

- Liquid/GEL/AGM/waterproof
- Open batteries SLI
- => From 20 to 150Ah

✓ **Multi-standard**

Test range

SAE norm:	200 to 1200 A
DIN norm:	110 to 670 A
IEC norm:	130 to 790 A
EN norm:	180 to 1254 A
CA norm (MCA) :	240 to 1440 A

✓ **Test with or without disconnecting the battery from the vehicle**

✓ **Test can be done on a discharged battery as low as 7V**

✓ **Protected against polarity inversions**

✓ **Instantaneous analysis** (result within 1 second)

- Battery voltage
- Available (real) power at start
- State of the battery

✓ **Digital display**

Starter Test

- ✓ **Carries out a test of the starting circuit**

Alternator circuit Test

- ✓ **Test of the load voltage.**

✓ **ABS body** (acid-proof)

✓ **Power supply** : Without battery, powered by the battery to be tested

✓ **Operating Temperature range** : 0°C to 50°C

✓ **Dimensions** : 12 x 7 x 15 mm **Weight** : 250 g.

