

The TRIMIG 305-4S DV 230-400V is the ideal 3-phase "synergic" welding machine for locksmith work, maintenance and semi-industrial production work.

Suitable for welding steel, stainless steel and aluminium, it is recommended for intensive professional use up to $\varnothing 1.2\text{mm}$ ($\varnothing 1.6\text{mm}$ occasionally) using its 4 roller wire feeder.

MACHINE

In synergic mode, the setting is quick and easy. The microprocessor will automatically select the optimum wire speed and other welding parameters.

3 MODES AVAILABLE

- ✓ **2T:** 2 times
- ✓ **4T:** 4 times (to weld extensively without having to hold the trigger)
- ✓ **Spot:** Spot welding with adjustable spot diameter

2 SETTINGS: SYNERGIC OR MANUAL

- ✓ **Synergic:** The best results without adjusting the wire speed



Just select:

- The wire type
- The wire diameter
- The power using the two control knobs

TRIMIG 300-4S selects the optimum wire speed for you.



Ref. 033832
(Without accessories)

Additional accessories
Ref 040946
Torch Grip 350A- $\varnothing 1,2$ (4m)



Ref 043817
Earth clamps (4m)



The settings (wire diameter, wire type and mode) entered in this mode are kept in memory and will be ready to use for the next job.

- ✓ **Manual:** Manual adjustment of the wire speed.

DESIGNED FOR HEAVY DUTY WORK

The TRIMIG 300-4S is suitable for $\varnothing 200 / \varnothing 300\text{mm}$ wire reels. It is equipped with a 4 roller wire-feeder, ideal for feeding soft aluminium wires as well as for the most demanding jobs.



CE EN 60974-1

50/60Hz	AM	min>max	\varnothing mm GAS NO GAS	\varnothing mm 100 200 300	Electronic Control	équipé d'origine original equipment originalausstattung equipamiento de fabrica	EN60974-1 (40°C)	U ₀	cm kg	POWER GENERATOR (+15%)
400V	16A	35 300	0,8 1,2	✓ ✓	✓	1,0/1,2	240A 35%	17 39	50x90x88cm 90kg	15kVA