


TRADITIONAL WELDING MACHINE FOR INTENSIVE USE

- ❖ Power input: Triphase 400V
- ❖ Traditional 300 DC Accepts welding electrodes from Ø 1,6 to 5 mm
- ❖ Traditional 400 DC / 500 DC Accepts welding electrodes from Ø1,6 to 6 mm
- ❖ Very easy-to-use
- ❖ Setting by turning the knob
- ❖ Strong ventilated steel casing
- ❖ Thermal overload protection
- ❖ Selectable welding output power



	 50/60Hz		I₂ MMA	EN60974-1 (40°C)		 U ₀	cm kg 
				I _A (60%)	X% (I ₂ max)		
TRADITIONAL 300 DC - REF.015005	400V 3~	20A	45A ▷ 225A	140A	20%	63V	86x44x59cm / 92Kg
TRADITIONAL 400 DC - REF.015012	400V 3~	25A	80A ▷ 290A	180A	20%	63V	86x44x59cm / 106Kg
TRADITIONAL 500 DC - REF.015227	400V 3~	32A	90A ▷ 370A	230A	20%	63V	86x44x59cm / 124Kg

CE EN 60 974 -1

MADE IN ITALY

ACCESSORIES (options)

ELECTRODES HOLDER + CABLE

300A - Ø35 mm² - 4m - REF.043862 (x1)500A - Ø50 mm² - 4m - REF.043879 (x1)

EARTH CLAMP + CABLE

300A - Ø25 mm² - 4m - REF.043800 (x1)400A - Ø35 mm² - 4m - REF.043817 (x1)500A - Ø50 mm² - 4m - REF.043824 (x1)

NOTE :