

- Welding unit with inverter technology piloted bt microprocessor.
- The arc dynamic of the product is unique and revolutionary on the market.
- Can be used with all types of electrodes: rutile, stainless steel, cast iron in direct current.
- Very handy, thanks to its small weight (2.5 kg), its highly reduced volume and its very low consumption (plug16A with AM fuse)



MMA

- ✓ Immediate start thanks to its very high no-load voltage
- ✓ Constant welding power
- ✓ Very smooth melting due to the direct current.
- ✓ Insensate to supply current fluctuations or to the arc length.
- ✓ Very good penetration and perfect arc stability.



REF.029958

Delivered in cardboard with
 • **Earth cable** (1,6m/ø10mm²)
 • **Electrode holder** (1,6m/ø10mm²)

REF.029941

Delivered in suitcase with
 • **Earth cable** (1,6m/ø10mm²)
 • **Electrode holder** (1,6m/ø10mm²)
 • **Hand mask**
 • **Chipping hammer**

ASSETS

- ✓ **ARC FORCE** : Punctual increase of the current in difficult welding situation
- ✓ **HOT START** : Increased power at start
- ✓ **ANTI STICKING** : anti sticking process

CE EN 60974-1

50/60Hz	AM	I ₂ MMA	1h	MIN 20'	EN60974-1 (40°C)	U ₀	mm ²	cm/kg	Protected & compatible POWER GENERATOR (40-15%)						
		ø1,6 ø2 ø2,5 ø3,2 ø4 ø5	I _A (50%)	X _g (I ₂ max)											
230V	10A	10A ▽ 80A	62	50	20	-	-	-	31A	6%	85V	10/25	10x14x23 / 2,5	3kW	3,7kVA