

## 'AIR JACK CAR – AIR JACK VAN

**AIR JACK CAR 2T**  
Ref.052550



**AIR JACK VAN 2T**  
Ref.052567



### Extremely flat

Thanks to their **low thickness**, the Air Jack products **slide under all vehicles**.

### Simple to use

**2 commands** : 1 command to inflate the Air jack and lift the vehicle; 1 command to deflate the Air jack and lower the vehicle.

### Fast

The Air Jack products **reduce significantly the time required to lift a vehicle**, as compared to a traditional jack.

### Very good stability

Their telescopic column combined with a wide base provide these products with a **perfect stability**. The Air Jack products will match perfectly the movements of the vehicle during the lifting phase.

### Totally secured

Equipped with a **safety valve**, the Air Jack products are **protected against any overweight or overpressure incidents**, making it totally secure for the operator.

### Portable

Lightweight, the Air Jack products can easily be carried around.

### No need for specific compressed air input for the jack

In the « lift » position, the compressed air network can be disconnected allowing using other pneumatic equipment in the meantime with the same air input.

Ref.	Designation	Capacity (kg)	Min. Height (mm)	Max. Height (mm)	Air pressure (Bar.max)	Weight
052550	AIR JACK CAR	2000	100	295	10,0	14,0
052567	AIR JACK VAN	2000	125	400	10,0	17,0